



A2414500

1. WHEN MACHINING VACUUM PARTS, USE SILICONE AND SULPHUR-BASED CUTTING FLUIDS IS PROHIBITED. USE ONE OF THE FOLLOWING:
A) CIMCOOL 5 STAR 49
B) TRIM SOL.
2. THIS IS A UHV PART. THE PART MUST GO THROUGH A MULTIPLE STEP CLEANING PROCESS INVOLVING DEGREASING, WASHINGS AND DRY NITROGEN BLOWDOWN.
3. KEEP THE PART CLEAN AND WRAP FOR UHV PACKING WITH ALUMINUM FOIL.
4. DIMENSIONS IN [] ARE MILLIMETERS AND FOR REF. ONLY
5. SURFACE ROUGHNESS ⁶³

MATERIAL / SPEC	QT
-----------------	----

PROPERTY OF _____

ANAL LABORATORY

ADVANCED PHOTON SCIENCEFOR MOUNT ASSEMBLY

FOR MOUNT ASSEMBLY EMBL Y FOR SPICAT

1300mm MIRROR

BRG TABLE-LOWERBRO TABLE-LOWER

DRAWING NUMBER

04105001203 350002 0

SYM	CHANGE DESCRIPTION	BY	CHKD	DATE